

## Hardware



### Central Management Station

MODEL	L	M	S
<b>Hardware</b>			
Revision	4.0	4.0	4.0
CPU	12 Cores, 3.5 GHz	6 Cores, 3.5 GHz	6 Cores, 2.3 GHz
Memory	64 GB ECC	32 GB ECC	32 GB ECC
Network interfaces min.	2 x 1 Gbit/s + 2 x 10 Gbit/s	4 x 1 Gbit/s	2 x 1 Gbit/s + 2 x 10 Gbit/s
Network interfaces max.	14 x 1 Gbit/s + 2 x 10 Gbit/s	10 x 1 Gbit/s	6 x 1 Gbit/s + 2 x 10 Gbit/s
Network interfaces 10 Gbit/s max.	2 x 1 Gbit/s + 14 x 10 Gbit/s <sup>1</sup>	4 x 1 Gbit/s + 4 x 10 Gbit/s <sup>1</sup>	-
Flash Drive	3 x 500 GB SSD	3 x 500 GB SSD	500 GB SSD
RAID level	1	1	-
DVD-ROM Drive	-	-	-
Graphics Connector	VGA	VGA	VGA, DVI, 2 x DisplayPort
Serial Ports	2	1	2
USB Port	3.0	3.0	3.0
Smartcard Slot	Format ID-1	Format ID-1	Format ID-1
<b>Chassis</b>			
Power Supply	2 x 650 W	2 x 800 W	1 x 250 W
Power consumption load	340 W	165 W	100 W
BTU/h load	1156	563	340
Fixture	19" rackmount	19" rackmount	19" rackmount
Width	430 mm (19")	430 mm (19")	430 mm (19")
Height	88 mm (2 U)	44 mm (1 U)	44 mm (1 U)
Depth	500 mm	399 mm	460 mm
Weight	13 kg	8.1 kg	6 kg
Weight (incl. Packaging)	19 kg	10.0 kg	12 kg

<sup>1</sup> 1/10 Gbit/s RJ45 or SFP+ with optional multi- or mono-mode fiber optic transceiver

## Hardware



L	ENVIRONMENT OPERATION	ENVIRONMENT STORAGE
Voltage	100 - 240 V AC, 60 - 50 Hz, 8 - 4 A, connector 2x IEC-C14	-
Temperature	10 - 35 °C	-20 - 70 °C
Humidity	20 - 80 % non condensing	10 - 80 % non condensing
Shock	25 G: 2 ms	300 G: 2 ms
Vibration	5 - 500 Hz: 0.5 G	0 - 500 Hz: 3 G
Norms	CE	-

M	ENVIRONMENT OPERATION	ENVIRONMENT STORAGE
Voltage	100 - 240 V AC, 60 - 50 Hz, 5.5 A, connector 2x IEC-C14	-
Temperature	10 - 35 °C	-40 - 60 °C
Humidity	8 - 90 % non condensing	5 - 95 % non condensing
Shock	20 G: 2 ms	10 - 20 G: 10 ms
Vibration	5 - 200 Hz: 0.25 G	5 - 200 Hz: 0.5 G
Norms	CE, UL, FCC, ICES, COC	-

S	ENVIRONMENT OPERATION	ENVIRONMENT STORAGE
Voltage	100 - 240 V AC, 60 - 50 Hz, 4 - 2 A, connector 1x IEC-C14	-
Temperature	10 - 35 °C	-20 - 70 °C
Humidity	20 - 80 % non condensing	10 - 80 % non condensing
Shock	25 G: 2 ms	300 G: 2 ms
Vibration	5 - 500 Hz: 0.5 G	0 - 500 Hz: 3 G
Norms	CE	-