

Hardware



Industrial Firewall



MODEL	XSi
Hardware	
Revision	2.0
CPU	2 Cores, 1.0 GHz
Memory	2 GB
Network interfaces min.	4 x 1 Gbit/s
Network interfaces max.	4 x 1 Gbit/s
Network interfaces 10 Gbit/s max.	-
Flash Drive	16 GB
DVD-ROM Drive	-
Graphics Connector	-
Serial Ports	2
USB Port	2.0
Smartcard Slot	optional extern
Performance	
Firewall TCP	940 Mbit/s ¹
Firewall UDP	1970 Mbit/s ²
Chassis	
Power Supply	optional extern
Power consumption load	15 W
BTU/h load	51.15
Fixture	DIN rail mount
Width	153 mm
Height	50 mm
Depth	110 mm / 130 mm (with Phoenix connector)
Weight	0.8 kg
Weight (incl. Packaging)	2.1 kg

¹ tcp packets: 1448 byte

² udp packets: 1500 byte bidirectional

Hardware



XSi	ENVIRONMENT OPERATION	ENVIRONMENT STORAGE
Voltage	24 V DC (9 - 36 V DC), min. 0.2 A, max. 1.5 A	-
Temperature	0 - 60 °C at 50 % humidity, non condensing	-20 - 70 °C at 50 % humidity, non condensing
Humidity	20 - 80 % non condensing	10 - 90 % non condensing
Shock	1 G 11 ms half-sine	10 G 11 ms half-sine
Vibration	5 - 500 Hz, PSD 0.02 G ² /Hz, 0.5 Grms	5 - 500 Hz, PSD 0.02 G ² /Hz, 0.5 Grms
Norms	CE	-